

GREEN FILM

POLYOLEPHIN FILM FORMULATED BY R&D -CHEMICAL

QUALITY - TECHNOLOGY - APPLICATIVE EXPERIENCE - HIGH PERFORMANCES

-  **EXTREMELY TRANSPARENT**
-  **RECYCLABLE AND ECOLOGICAL**
-  **IDEAL FOR MANUAL AND AUTOMATIC HEAT-SHRINKING MACHINES**
-  **ITS PROPERTIES DO NOT CHANGE EVEN AFTER LONG STORAGE**
-  **ITALIAN PRODUCTION**
-  **100% MADE IN ITALY**

GREAT NEWS!

GREEN FILM
52% A BIO BASED
13-15-19 μ

GREEN FILM LIGHT
ONLY 9 μ THICKNESS
2,300 m in 1 roll

PROPERTY	UNITY	METHOD	PROPERTY	UNITY	METHOD
tear resistance	N	ASTM D-1922	tensile strength	N/15 (mpA)	ASTM D-882
resistance to welding	N/15 mm	internal test	20° shine	%	ASTM D-2457
friction coefficient		ASTM D-882	opacity	%	ASTM D-1003
rigidity module	MPa	ASTM D-882	water vapor permeability	g/m ² /24 h-38°C-100% HR	ASTM E-96
stretch	%	ASTM D-882	oxygen permeability	cm ³ /m ² /24 h/atm-23°C-50% HR	ASTM D-3985-81

QUALITY AND CHARACTERISTICS OF GREEN FILM ARE GUARANTEED BY A CONSTANT QUALITY CONTROL

GREEN FILM – CX	AVAILABLE WIDTH BANDS										
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
thickness	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
• standard measures always available 7 μ in stock	200	250	300	350	400	450	500	550	600	700	800
15 μ	•	•	•	•	•	•	•	•	•	•	•
19 μ	•	•	•	•	•	•	•	•	•	•	•

• on request also 25 μ

www.italdibipack.com

**A GROUP IN
CONTINUOUS EVOLUTION**

info@italdibipack.com

via Europa, 35 - 20010 Pogliano Milanese (MI)
tel: +39 02 9396461 - fax: +39 02 93549494

